

TENARIS.010A2

DELPHION**Select CR****RESEARCH****PRODUCTS****INSIDE DELPHION****Log Out****Work Files****Saved Searches****My Account**

Search: Quick/Number Boolean Advanced Derwent

Help


The Delphion Integrated View


Get Now: ☒ PDF | [File History](#) | [Other choices](#)Tools: Add to Work File: [Create new Work File](#) View: [INPADOC](#) | Jump to: [Top](#) **Title: JP63230847A2: LOW-ALLOY STEEL FOR OIL WELL PIPE EXCELLENT IN CORROSION RESISTANCE****Derwent Title:** Corrosion resistant low alloy steel for oil well piping - contains carbon, silicon, manganese, aluminium, nitrogen and opt. chromium, molybdenum, niobium, vanadium, boron [[Derwent Record](#)]**Country:** JP Japan**Kind:** A DOC. LAID OPEN TO PUBL. INSPEC. [PUBLISHED FROM 1971 ON] ⁱ**Inventor:** OKADA YASUTAKA;
IKEDA AKIO;**Assignee:** SUMITOMO METAL IND LTD
[News, Profiles, Stocks and More about this company](#)**Published / Filed:** 1988-09-27 / 1987-03-20**Application Number:** JP1987000067023**IPC Code:** Advanced: [C22C 38/00](#); [C22C 38/06](#); [C22C 38/38](#);
Core: [more...](#)
IPC-7: [C22C 38/00](#); [C22C 38/06](#); [C22C 38/38](#);**Priority Number:** 1987-03-20 JP1987000067023**Abstract:** PURPOSE: To develop a low-alloy steel excellent in strength and corrosion resistance, by minimizing the precipitation of AlN by reducing respective contents of N and Al in a low-alloy steel for oil well pipe to traces.

CONSTITUTION: A steel tube for use in oil fields and gas fields, such as oil well pipe, oil transport pipe, etc., is manufactured by using a low-alloy steel stock which has a composition containing, by weight, 0.15W0.45% C, 0.10W1.0% Si, 0.3W1.8% Mn, <0.010% sol. Al, <0.0020% N, and <0.0050% AlN or further containing one or more kinds among 0.05W2.00% Cr, 0.02W0.80% Mo, 0.005W0.20% Nb, 0.005W0.20% V, and 0.0001W0.0030% B. By the above composition, the quantity of the fine precipitates of AlN is minimized, and the low-alloy steel as an oil well pipe stock excellent in resistance to sulfide stress corrosion cracking in a high-strength region can be manufactured.


COPYRIGHT: (C)1988,JPO&Japio

INPADOC Legal Status: None **Get Now:** [Family Legal Status Report](#)**Family:** [Show 24 known family members](#)**Forward References:** **Go to Result Set:** [Forward references \(1\)](#)

PDF	Patent	Pub.Date	Inventor	Assignee	Title
	US5117874	1992-06-02	Ochiai; Ikuo	The Furukawa Electric Co., Ltd.	Flexible fluid transport pipe having hydrogen-induced cracking resistant high-strength steel

Other Abstract Info: [DERABS C88-312366](#) [DERC88-312366](#)[View Image](#)

1 page



[Nominate this for the Gallery...](#)

Copyright © 1997-2009 Thomson Reuters

[Subscriptions](#) | [Web Seminars](#) | [Privacy](#) | [Terms & Conditions](#) | [Site Map](#) | [Contact Us](#) | [Help](#)